



| REV. | ECN NO. | DESCRIPTION | DATE | DESIGN |
|------|---------|-------------|----------|--------|
| A0. | /. | 新版发行 | 20.05.04 | Yang |
| A1. | /. | 重新核对图面 | 21.01.06 | LiHui |

| PIN数 | A±0.1 | B±0.1 | C±0.1 |
|------|-------|-------|-------|
| 2P | 4.30 | 1.00 | 3.25 |
| 3P | 5.30 | 2.00 | 4.25 |
| 4P | 6.30 | 3.00 | 5.25 |
| 5P | 7.30 | 4.00 | 6.25 |
| 6P | 8.30 | 5.00 | 7.25 |

Specifications:

- Rated Voltage : 50V AC/DC
- Rated Current : 1A AC,DC
- Withstand Voltage : 200V AC/minute
- Contact Resistance : 50mΩ(MAX.)
- Insulation Resistance : 100MΩ(MIN.)
- Storage Temperature Range:-40°C~+85°C;
- Operation Temperature Range:-25°C~+70°C;

| 3 | 插片 | 黄铜H65 | 镀镍锡 | |
|----|----|-------|-------|----|
| 2 | 插针 | 黄铜H65 | 镀镍锡 | |
| 1 | 底座 | LCP | 本色 | |
| 序号 | 品名 | 材质 | 电镀/颜色 | 备注 |

深圳市虹成电子有限公司

| | | |
|--|----------------------------|--------------------------------|
| UNLESS OTHERWISE, GENERAL TOLERANCE: X. xxx ±0.05 X. xx ±0.15 X. x ±0.25 | NAME: 针座1.0立贴6P编带 | P/N: HCZZ0039-6 |
| | DWG NO: | |
| ANGULAR: X. xx° ±1° X. x° ±3° X. ° ±5° | THIRD ANGLE PROJECTION | UNIT: SCALE: SIZE: SHEET: REV. |
| | DRAWN: | CHECKED: APPROVED: |

