




标记 MARK	ECN编号/变更内容 ECN NO/DEFINITION	修改 REVISE	日期 DATE	核准 APPROVE

Pin	DIM A	DIM B
2	7.50	0.00
3	10.00	2.50
4	12.50	5.00
5	15.00	7.50
6	17.50	10.00
7	20.00	12.50
8	22.50	15.00
9	25.00	17.50
10	27.50	20.00
11	30.00	22.50
12	32.50	25.00
13	35.00	27.50
14	37.50	30.00
15	40.00	32.50
16	42.50	35.00





2PIN



技术要求:

适应基板厚度: 1.2mm~1.6mm
 温度范围: -25°C~85°C
 额定电压: 250V AC/DC
 额定电流: 3A
 接触电阻: ≤0.01Ω
 绝缘电阻: ≥1000MΩ
 耐 压: 1000V AC/minute



2	插针	铜	镀锡	
1	基座	PA66	米色	
序号	品名	材质	电镀/颜色	备注

深圳市虹成电子有限公司 品名 TITLE 料号 PART NO		针座	
		HCZZ0126-4	
GENERAL TOLERANCES (UNLESS SPECIFIED)		比列 SCALE	1:1
X.X ±0.35 X* ±3.00'		单位 UNIT	MM
X.XX ±0.25 X.X* ±2.00'		张数 PART NO	1 OF 1
X.XXX ±0.15 X.XX* ±1.00'		版本 REV	A
制图 DRAW		审核 CHECKED	夏操云
批准 APPROVE		赵亮亮	

